



10 YEAR* WARRANTY

IDEAL LOGIC+ 30 BOILER INTERNAL

The Logic+ 30 Condensing System Boiler provides excellent energy saving, and performs quietly in your home.

- Made in the UK
- 1:4 Modulation rate
- Built in Frost Protection
- Large backlit LCD display
- Aluminium Silicon Heat Exchanger
- Light weight and compact design
- Quiet operation
- User friendly control panel





Hydronic Heating NSW
866 Bourke St, Waterloo.
NSW 2017

www.hydronicnsw.com.au

IDEAL LOGIC+ 30 BOILER INTERNAL


Technical Information



C



General Data		30 System	
Gas Supply - NG/LPG		1.13kPa / 2.75kPa	
Gas Supply Connection		1/2"	
Flow Connection		3/4"	
Return Connection		3/4"	
Flue Terminal Diameter	mm	100	
CO2 Content (± 0.7) NG/LPG	Max. CH	8.9%/10.7%	
	Min. CH	8.7%/10.4%	
Maximum Working Pressure (Sealed Systems)	kPa	250	
Electrical Supply		230 V ~ 50 Hz	
Power Consumption	W	100	
Min. thermostat cable size		1mm twin active	
Water Content	Litre	ne 1.2	
Height	mm	mm 700	
Width	mm	395	
Depth	mm	278	
Packaged Weight	kg	31.5	
Installation Weight	kg	26.1	
Performance Data		Min	Max
Boiler output - Mean 70°C	kW	6.1	30.3
Boiler output - Mean 40°C	kW	6.4	31.0
Gas Consumption	MJ/h	23.01	119.41
Boiler Efficiency	%	% 91.1	



* Please contact Hydronic Heating NSW for terms & conditions

6 1300 267 583



Hydronic Heating NSW 866 Bourke St, Waterloo. NSW 2017 www.hydronicnsw.com.au

☑ info@hydronicnsw.com.au

