

MANUFACTURED BY:

STIEBEL ELTRON



Looking for an
energy-efficient
solution
for your home?



5 YEAR*
WARRANTY

ELECTRIC HYDRONIC SOLUTIONS

Look no further than the WPL 25 AC/ACS air source hydronic heat pump from Hydronic Heating NSW. With its exceptional COP of 5 and heating output of 14kW, the WPL 25 AC/ACS is the perfect choice for underfloor heating in new builds or use with radiators



Outdoor installation to harvest energy from the air and turn it into comfortable heating and cooling for your home.



Suitable heat source for new and existing homes in new builds heating output matches the standard Australian home



Suitable for use with underfloor heating and radiators - Up to 65C flow temperature



Increased efficiency through enhanced saturated vapour injection.



Energy efficient inverter technology



Quiet operation

☎ 1300 267 583

📍 Hydronic Heating NSW
866 Bourke St, Waterloo,
NSW 2017




🌐 www.hydronicnsw.com.au
✉ info@hydronicnsw.com.au

Outputs & Dimensions

		WPL 25 AC	WPL 25 ACS
Energy efficiency class		A++	A++
Rated voltage	V	400 (3 phase)	230 (Single phase)
Output at A7/W35 (EN 14511)	kW	14	14
Coefficient of performance at A7/W35 (EN 14511)		5.09	4.81
Cooling output	kW	14.88	14.88
Cooling capacity factor		3.76	3.76
Sound power level (EN 12102)	dB(A)	54	54
Sound pressure level at 5 m distance in a free field	dB(A)	32	32
Max. Temperature output on the heating side	°C	65	65
Height	mm	1045	1045
Width	mm	1490	1490
Depth	mm	593	593
Weight	kg	175	175

		WPL 25 AC	WPL 25 ACS
A	Condensate drain	Ø mm	22
B	Flow	Ø mm	1"
C	Return	Ø mm	1"
D	Air intake		
E	Air discharge		



DIMENSIONS



- Allowance also required for a buffer tank to optionally sit beside the heatpump.

Dimensions: 700 diameter 1400 height

MINIMUM CLEARANCES



Never install the appliance in a recess. Two sides of the appliance must remain exposed.

Maintain the minimum clearances to ensure trouble-free operation of the appliance and facilitate maintenance work.

MANUFACTURED BY:

STIEBEL ELTRON

HEAT PUMP MANAGER (REQUIRED)



The WPM is the control centre of any STIEBEL ELTRON heat pump system, enabling the entire system to be monitored and controlled.

ROOM BASED REMOTE CONTROL



The FET remote control displays all the information you need to set the right temperature in your living room. Paired with a heat pump manager, you can control multiple zones.

INTERNET-SERVICE GATEWAY



The ISG web allows for an automated transfer of heat pump performance data to the internet service portal and remote service report. Homeowners have the option to control settings online through the STIEBEL ELTRON app.

INSULATED PUMP ASSEMBLY



The WPKI-HK E suits a heat pump installation with one heating circuit. Includes circulation pump, shut-off valves with thermometer and gravity brake as well as opening mechanism.